

FICHA TÉCNICA PAVIMENTO TARAFLEX SURFACE

CARACTERÍSTICAS TÉCNICAS.

DESCRIPCION				
Dry-Tex System				
Eco-fit System				
PRODCUTO DESCRIPTION				
Surface treatment	-	-	-	Triple-Action ProtecSol®
Surface complex	-	-	-	D-Maxtm
Foam	-	-	-	-
Thickness	EN 428	-	Mm	2.1
Weight	EN 430	-	Kg/m2	2,9
Length	EN 426	-	Lm	30 Max
Width	EN 426	-	Lm	1.5
SPORT PROPERTIES				
Shock absorption	EN 14808	≥25	%	-
Vertical deformation	EN 14809	≤ 3.5	Mm	-
Energy return	NF P 90 203	≥ 0.31	m/s	-
Sliding coefficient	EN 13036-4	80 to 110	-	80 - 110
Ball Bounce	EN 12235	≥ 90	%	≥ 90
Ball speed	UEFA	50 to 65	Cm	-
	ITF	-	-	-
TECHNICAL CHARACTERISTICS				
Abrasion resistance	EN ISO 5470-1	≤ 1000	Mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	≥8
Indentation resistance	EN 1516	≤ 0.5	Mm	≤ 0.5
CLASSIFICATION				
Fire	EN 13501-1	-	-	Bfl-s1
Special treatment	-	-	-	Sanosol®
CE	EN 14 904 2006			Fire Sliding Coefficient Abrasion Resistance Resistance to roaling load